Trail Difficulty Rating System (INCLUDING ADAPTIVE MOUNTAIN BIKE - aMTB)

	WHITE	aMTB WHITE	GREEN	aMTB GREEN	aMTB GREEN SQUARE	BLUE	aMTB BLUE	BLACK	aMTB BLACK	DBL. BLACK	aMTB DBL BLK	aMTB DBL. BLK
	\bigcirc	ð		ð	ð		ð				E	
TRAIL WIDTH: (ave/min)	72"+	72"+	36"+	72"/60"	66"/54"	24"+	60"/48"+	12"+	48"/40"	6"+	44"/38.5"	<38.5"
TREAD SURFACE:	hardened or surfaced	hardened or surfaced		firm and stable	mostly stable some variability	mostly stable some variability	mostly stable some variability	widely variable	widely variable	widely variable and unpredictable	widely variable and unpredictable	widely variable and unpredictable
OBSTACLES (TTF):	no obstacles	no obstacles	unavoidable obstacles 2" or less	obstacles full width 2" or less / no asymmetrical tread areas	obstacles full width 5" or less / partial width 2" or less	unavoidable obstacles 8" or less	obstacles full width 8" or less / partial width 3" or less	unavoidable obstacles 15" or less	obstacles full width 12" or less / partial width 6" or less	unavoidable obstacles 15" or less	obstacles full width 12" or less / partial width 10" or less / assistance recommended	impassable obstacles / assistance required
UNAVOIDABLE BRIDGES: (wider if not straight)	72"+	72"+	36"+	60"+	60"+	24"+	54"+	24"+	48"+	<24"	40"+	<38.5"
MAX TRAIL GRADE:	10%	10%	15%	15%	20%+	15%+	20%+	15%+	25%+	20%+	20%+	20%+
CAMBER:		level		only enough to drain	Some off camber possible : max 20 deg		Some off camber possible : max 20 deg		Some off camber likley: max 30 deg		Off camber certain max ??	Off camber certain max ??
MIN FLAT CORNER RADIUS:	2.5m	7.5m (24.5 ft)	2.4m	6m (20 ft)	6m (20 ft)		6m (20 ft)		6m (20 ft)		4.5m (15 ft)	4m (13 ft)
MIN BERM CORNER RADUS:		n/a		n/a	6m (20 ft)		4.5m (15 ft)		4.5m (15 ft)		<4m (13 ft)	< 3m (10 ft)
RECOMMENDED EQUIPMENT: *Riders may choose to take equiment on trails falling outside of recommended trail difficulty at their own risk, but in this case support rider always recommended.		₹							0 .40		○ ≰°	⊖ ττόί